



Bi-fold door operation & maintenance instructions



Camel Glass

Bi-fold door operation & maintenance instructions

Opening the door

Insert the key into the lock barrel and rotate to unlock, then remove the key.

Press the lever handle down and open the door, folding it back onto the magnetic catch on the adjacent door to secure. If operated as a separate leaf, we recommend that a restraint of some type be installed to secure the door in the open position.

To open the remaining doors, rotate the slave handle 180 degrees to release the shoot-bolts.

For open out doors - Push the doors open above the D handle and guide the doors open until fully open.

For open in doors - Gently pull on the slave D handle to start the doors in motion. Once sliding, release the handle and guide the doors to the fully open position.

Closing the door

Pull the open doors towards the closed position, sliding them along the running track, utilising the D pull handle to pull the doors into the fully closed position. Rotate the slave handle 180 degrees, to engage the shoot bolts and lock the slave doors in the closed position.

Close the lead door by pulling on the door handle, releasing it from the magnetic catch.

Lift the handle up to engage the locks, insert the key and turn to lock, remove the key.

Maintenance instructions

Lubrication of moving parts

Your new bi-fold contains mechanical moving parts that will need to be lubricated periodically. This will include the hinges, handles, lock and trolley wheels both in the top and bottom track. Lubricate with a silicone spray or grease and wipe away excess with a non-abrasive cloth.

Extra care should be taken in Hazardous environments, such as marine and indoor swimming pools, to ensure that all moving parts are protected, application of protective lubricants twice a month is advised.

Washing of profiles.

Use a light, soapy solution (such as a diluted baby bath product) and a non-abrasive cloth to wipe dirt from the window frames. Washing up liquid is not recommended and do not use solvent based cleaning agents or abrasive agents.

Extra care should be taken in Hazardous environments, such as marine and indoor swimming pools, here windows and hardware should be washed down on a weekly basis with fresh water as it is common for harmful deposits to build up and potentially damage your windows.

Gaskets

Use a light soapy solution and non-abrasive cloth to gently clean these, do not use solvent based cleaning products on the seals.

